



## HD 12 VV / HD 12 VT

**HD 12 VV** - Articulated tandem roller with two vibratory drums

**HD 12 VT** - Articulated combi roller with vibratory drum



- ▶ Optimum front view due to concaving front end
- ▶ Ergonomic driver platform
- ▶ Modern instrument panel
- ▶ Low machine height
- ▶ 3-point swivel joint for optimum driving comfort
- ▶ Central suspension point
- ▶ Convenient maintenance and service



# HD 12 WV / HD 12 VT

HD 12 WV - Articulated tandem roller with two vibratory drums  
HD 12 VT - Articulated combi roller with vibratory drum



		HD 12 WV	HD 12 VT
<b>Weights</b>			
Operating weight with ROPS	kg	2695	2595
Operating weight, max.	kg	3410	3320
Axle load, front/rear	kg	1335/1360	1340/1255
Load per tyre, rear	kg		313,75
Static linear load, front/rear	kg/cm	11,2/11,4	
Static linear load, front	kg/cm		11,2
French classific., data/class		11,4/PV3	11,2/PV2.PLO
<b>Machine dimensions</b>			
Max. working width	mm	1250	1220
Turning radius, inside	mm	2370	2370
Size of tyres, rear			205/60-R15
<b>Diesel engine</b>			
Manufacturer		KUBOTA	KUBOTA
Type		D1503-M-E3B	D1503-M-E3B
Number of cylinders		3	3
Power rat. ISO 14396, kW/PS/rpm		22,9/31,1/2700	22,9/31,1/2700
Power rating SAE J1349, kW/HP/rpm		22,9/30,7/2700	22,9/30,7/2700
Emissions standard EU/USA		III A / Tier 4i	III A / Tier 4i
<b>Drive</b>			
Hydrostatic drive, front/rear		Hydr. motor/hydr. motor	Hydr. motor/hydr. motor
Speed, infinitely variable	km/h	0 - 12,0	0 - 12,0
Climbing ability, vibration on/off	%	30/40	30/40
<b>Vibration system</b>			
Hydrostatic drive, Vibration, front + rear, switched separately and together (VV), Automatic vibration switch-off function at excessive speed, Vibration, switched manually and automatically			
<b>Vibration</b>			
Vibration frequency, front, I/II	Hz	67/52	67/52
Vibration frequency, rear, I/II	Hz	67/52	
Amplitude, front, I/II	mm	0,52/0,52	0,52/0,52
Amplitude, rear, I/II	mm	0,52/0,52	
Centrifugal force, front, I/II	kN	52/32	52/32
Centrifugal force, rear, I/II	kN	52/32	
<b>Steering</b>			
Steering, type		Articulated steering	Articulated steering
Steering, actuation		hydrostatic, steering wheel	hydrostatic, steering wheel
Steering angle +/-	°	32	32
Oscillation angle +/-	°	8	8
<b>Sprinkler system</b>			
Water sprinkler, type		Pressure	Pressure
Actuation, sprinkling		interval/manual	interval/manual
Water tank, capacity	L	180	180
Additive sprinkling, type			Pressure
Actuation, additive sprinkling			Push button
Additive tank, capacity	L		18

**Equipment**  
Crab steering up to 50 mm, Spring-mounted driver seat, Comfort seat with seat belt, Operating hours counter, Indicator lights, Emergency stop switch

**Optional equipment**  
2 spotlights on ROPS, Back-up alarm, Rotating beacon, Special colour, Sunroof, Edge pressing and cutting equipment, Sound insulation

<b>Total length</b>	L	2460	2460
<b>Width</b>	B	1310	1310
<b>Total height</b>	H	2390	2390
<b>Wheel base</b>	A	1700	1700
<b>Roller drum width</b>	X	1200/1200	1200
<b>Drum diameter</b>	D	720/720	720
<b>Width over tyres</b>	Y		1000
<b>Diameter of tyres</b>	R		630
<b>Height loading, min.</b>	HI	1752	1752

